




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: H04Q 7/24	A1	(11) International Publication Number: WO 97/41699 (43) International Publication Date: 6 November 1997 (06.11.97)
<p>(21) International Application Number: PCT/SE97/00503</p> <p>(22) International Filing Date: 24 March 1997 (24.03.97)</p> <p>(30) Priority Data: 9601618-3 29 April 1996 (29.04.96) SE</p> <p>(71) Applicant (for all designated States except US): RADIO DESIGN INNOVATION AB [SE/SE]; P.O. Box 1223, S-164 28 Kista (SE).</p> <p>(72) Inventors; and</p> <p>(75) Inventors/Applicants (for US only): JOHNSON, Torbjörn [SE/SE]; Lidvägen 1, S-175 40 Järfälla (SE). STRÖM, Martin [SE/SE]; Vallmovägen 23, S-191 43 Sollentuna (SE).</p> <p>(74) Agents: HOLMQVIST, Lars, J., H. et al.; Albinh Holmqvist AB, P.O. Box 4289, S-203 14 Malmö (SE).</p>		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
<p>Published <i>With international search report.</i></p>		

(54) Title: SUBSCRIBER TERMINAL ARRANGEMENT



(57) Abstract

The invention relates to a subscriber terminal arrangement in a telecommunication system utilizing radio in the local loop. According to the invention, the arrangement comprises a subscriber terminal comprising a low power radio part, a pulse code modulation air interface and a low power paging channel for the call set-up procedure, a power supply part, and a user terminal comprising a hand-set and a dialling device. Ordinary telephone equipment, telephone fax, answering machine, data modem, PCs etc. may be connected to the subscriber terminal. In some cases the radio parts and telephony parts would be integrated in the same unit. The power supply part may be connected to an independent power supply unit comprising a power generator, e.g. solar panels and/or a wind generator, rechargeable batteries, and a control unit for controlling the charging procedure. The air interface is capable of supporting 64 kb/s PCM coding offering high quality audio, and/or variable data rates up to 64 kb/s.

从上表可以看出，与1990年相比，1995年我国的进出口总额增长了近一倍。

the first half of the twentieth century, the Soviet Union had been able to develop its own scientific and technical base, and to build up its own industrial capacity. This was achieved through a massive investment in science and technology, and through the development of a highly skilled and experienced workforce. The Soviet Union's scientific and technological achievements were recognized worldwide, and it became a major player in the global economy. The Soviet Union's scientific and technological achievements were also used to support its political and military goals, particularly during the Cold War period. The Soviet Union's scientific and technological achievements were also used to support its political and military goals, particularly during the Cold War period.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5

TITLE OF INVENTION: SUBSCRIBER TERMINAL ARRANGEMENT

10

FIELD OF THE INVENTION

The present invention relates to a subscriber terminal arrangement in a telecommunication system utilizing radio in the local loop. Radio in the Local Loop (RLL) is, substituting the copper lines in the local loop, the part of the network which is between the local exchange and the subscriber at home, with radio. The market for these applications is enormous, especially in the new growing economies like Far East, Russia and Brazil. Another growing market is the industrial countries where radio is the best solution for a new operator to compete with services in the local loop. Fixed subscriber terminals mean terminals which are not designed for mobility purpose. The terminal is placed in the home, office etc. and can be moved in the premises but not like hand held portable telephone. Ordinary telephone equipment, telephone fax, answering machine, data modem, PCs etc, could be connected to the terminal. In some cases the radio parts and telephony parts would be integrated in the same unit.

30

STATE OF THE ART

Today there are two main categories of radio subscriber terminals; for mobile use and fixed telephones connected to ordinary fixed network for telephony (POTS, Plain Ordinary Telephone System).

Today's radio subscriber terminals are power-consuming, expensive (due to standardized POTS interface), bad audio quality, no variable data rates etc. When the receiver is lifted there is a long delay before the dial tone is given. When mobile telephones are used, the subscriber have to

1996-1997 学年第一学期期中考试高二物理试题

and the condition of the animal varies with the degree of
the disease. The following table gives the approximate
percentage of the various forms of disease in the several
ages of cattle. The figures are based on a survey carried out in
various parts of England and Scotland in 1881. It shows that
about 40 per cent. of cattle are affected with some form of
disease, and that the percentage of diseased cattle increases
with age. The following table gives the approximate
percentage of diseased cattle in different ages of cattle.
The figures are based on a survey carried out in
various parts of England and Scotland in 1881.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

5

TITLE OF INVENTION: SUBSCRIBER TERMINAL ARRANGEMENT

10

FIELD OF THE INVENTION

The present invention relates to a subscriber terminal arrangement in a telecommunication system utilizing radio in the local loop. Radio in the Local Loop (RLL) is, substituting the copper lines in the local loop, the part of the network which is between the local exchange and the subscriber at home, with radio. The market for these applications is enormous, especially in the new growing economies like Far East, Russia and Brazil. Another growing market is the industrial countries where radio is the best solution for a new operator to compete with services in the local loop. Fixed subscriber terminals mean terminals which are not designed for mobility purpose. The terminal is placed in the home, office etc. and can be moved in the in the premises but not like hand held portable telephone. Ordinary telephone equipment, telephone fax, answering machine, data modem, PCs etc, could be connected to the terminal. In some cases the radio parts and telephony parts would be integrated in the same unit.

30

STATE OF THE ART

Today there are two main categories of radio subscriber terminals; for mobile use and fixed telephones connected to ordinary fixed network for telephony (POTS, Plain Ordinary 35. Telephony System).

Today's radio subscriber terminals are power-consuming, expensive (due to standardized POTS interface), bad audio quality, no variable data rates etc. When the receiver is lifted there is a long delay before the dial tone is given. 40 When mobile telephones are used, the subscriber have to

enter the number and thereafter have access to the radio channel (the send button is pressed).

The present invention solves the above-mentioned problem by providing an improved subscriber terminal arrangement.

5 The unique features of the subscriber terminals are based on:

- 64 kb/s PCM coding, (Pulse Code Modulation) which can offer: + high quality audio 7, 2 kHz-bandwidth compared with today's 3,1 kHz bandwidth for today's POTS (Plain Ordinary Telephony System);

10 + high quality audio 7, 2 kHz-bandwidth compared with today's 3,1 kHz bandwidth for today's POTS (Plain Ordinary Telephony System);

+ by multiplexing several (3-4) PCM channels, high quality hi-fi audio is offered

15 + variable data bit rates up to 64 kb/s

+ multiplexing of PCM channels to offer ISDN BRA, Integrated Services Digital Network, Basic Rate Access.

+ multi-user terminals with internal switch functionality in order to reduce the capacity requirement on the network.

20 - an independent power supply unit where there is no need of external power supply

25 - low power paging channel giving:

+ low power consumption

+ no delay for giving dial tone when receiver is lifted

30 - an integrated radio head in the antenna

SUMMARY OF THE INVENTION

Thus, the present invention provides a subscriber terminal arrangement in a telecommunication system utilizing radio in the local loop.

According to the invention, the arrangement comprises a subscriber terminal comprising a low power radio part, a pulse code modulation air interface and a low power paging channel for the call set-up procedure; a power supply part,

and a user terminal comprising a hand-set and a dialling device.

The invention is set forth in detail in the accompanying claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is described below with reference to the attached drawings, in which

Figure 1 is a block diagram of a first embodiment of the invention for ordinary POTS;

Figure 2 is a block diagram of a second embodiment of the invention in which the subscriber terminal equipment and the telephony equipment are integrated in the same physical unit;

Figure 3 is a block diagram of a third embodiment of the invention in which the radio part and the power supply unit are integrated in the same unit;

Figure 4 is a block diagram of a fourth embodiment of the invention including a multi-subscriber terminal; and

Figure 5 is a block diagram of a further embodiment of the invention in which the RF part is integrated with the antenna.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

There are two main groups of digital radio fixed subscriber terminals:

- the single user terminal family;
- a multi-user terminal family

All the terminals are based on low power radio with 0,1 W output. Both families could either be connected to an ordinary power supply unit, utilising the mains power supply, or an independent power supply unit. This unit is utilising solar/wind energy and rechargeable batteries. All terminals are utilising a low power paging channel for implementing the alert function. This sleep mode function, results in very low power consumption between calls. Therefore, the terminals could be used with powering from only solar/wind energy and batteries. The paging channel will be used in the call set up procedure, i. e. the dialled number will transferred immediately to the network at the same time as the radio

speech channels is allocated. This will result in no delay when the receiver is lifted and an immediate dial tone is given.

The paging function is similar to the POGSAG defacto standard which is capable to transfer 512 baud. For easy customer installation, the terminals are equipped with a LED indicator, showing red (no radio reception), yellow (not enough reception) and green (good radio reception).

In Figure 2, an embodiment of the single subscriber terminal family is shown.

As may be seen from Figure 1, the copper lines of an ordinary telephone network is replaced by an antenna equipment. The antenna equipment is connected to a subscriber terminal (Subs-terminal) which in turn is connected to the telephony equipment. The subscriber terminal includes the radio.

The terminal family is based on a digital radio with 0,1 W output. The service is based on 64 kb/s PCM coded radio channels. The telephony equipment at least consists of a hand-set and a dialling device, such as a key pad.

The following services would be offered:

- Ordinary POTS, including DTMF signalling (Dual Tone Multifrequency) and card cartridges etc etc
- Data over modem; 9,6, 14,4, 28,8 up to 64 kbit/s
- Dedicated data up to 64 kb/s

The ordinary telephone equipment is connected to a line interface (CCITT recommendation) which would be able to support an ordinary ringing generator and 2000 meter 2 wire copper cable i.e. 2/4 wire ordinary line interface.

There are three different versions of antenna installations:

- an antenna connected directly to the user terminal (omnidirectional, radiation in all directions)
- a separate antenna which could be placed in the window (omni/directional, radiation in a specific direction)
- an outdoor roof or wall/roof mounted antenna (directional)

There is an antenna connector at the subscriber terminal for connection of different types of antenna alternatives.

The present invention also provides a simplified sub-

scriber terminal, "Proprietary POTS". There are three different versions:

Version 1.

The main difference is the subscriber telephone equipment. One possibility is a telephony equipment, which is specially adapted to the subscriber terminal, without ringing generator and no lightning protection i.e., no standard POTS interface. The ringing signal is generated by a piezoelectric ringer in the hand-set. This would lead to a less complex implementation and therefore a reduction in cost because there is no standard line interface circuitry. The distance between the radio subscriber terminal and proprietary telephone equipment is maximum 50 meters. The power supply is 2 W DC. This solution would need a proprietary telephone equipment.

The same services as above is offered.

Version 2 is the most complicated and expensive. Another version is where the subscriber terminal equipment and the telephony equipment are integrated in the same physical unit. In order to save cost through simplicity there is no external line interface at all. The implementation is shown in Figure 2.

25

Version 3 is the most expensive.

There is one version where the radio part and power equipment are integrated in the same unit. This unit should be plugged directly into the wall. There are three input/output connections for: external antenna connection, a connection for the telephone equipment and one for DC input (battery backup or in case of no main supply) see Figure 3. There are two different versions of antenna installations:

- 35 - a separate antenna which could be placed in the window (omni/directional, radiation in a specific direction)
- an outdoor roof or wall/roof mounted antenna

(directional)

There is an antenna connector at the radio terminal for connection of different antenna alternatives.

One embodiment of the invention features a radio terminal which would provide ISDN Basic Rate Access, BRA. As an alternative the terminal can offer two ordinary POTS lines in accordance with the first embodiment.

5 Similarly, there are three different versions of antennas.

The invention provides a multi-subscriber family suitable for apartment buildings or offices, where it is desired to connect several user terminals.

10 This terminal family is also based on low power radio with 0,1 W output. The service is based on 64 kb/s PCM coded radio channel. There will be three different sizes serving up to 4, 8, 16 and 16-32 subscribers. All versions would provide the following services:

- 15 - Ordinary POTS
- Data over modem; 9,6, 14,4 28,8 up to 64 kbit/s
- Dedicated data up to 64 kb/s
- One version combining ISDN and POTS.

20 The later could in a flexible way be tailored for 16-32 subscribers. Depending on the number of subscribers there are 16-32 64 kb/s PCM radio channels which will basically serve up to 32 subscribers. There would even be a version which would be utilising concentration i. e. there are fewer 25 radio channel connections than the number of subscribers connected to the terminal. For example 30 PCM channels can support 290 customers (Traffic requirements: 70 mE/customer, 0,01 % blocking).

The principles of the multi-subscriber terminal family 30 is shown in Figure 4:

In order to not be independent of mains power supply (from the electricity company) there should be an option where the user terminals are connected to an independent power supply unit. The unit consists of:

35

- Power generator; solar panels or/and wind generator
- rechargeable batteries
- control unit, controlling the charging procedure

40 There would be one terminal version where the radio

frequency parts (RF parts) are moved from the subscriber terminal unit and are integrated together with the antenna. The radio parts in the RF unit are DC powered (Direct Current) by the subscriber terminal via the antenna cable.

5 Thus, the present invention provides an improved subscriber terminal arrangement having the advantages stated above. Of course, many variations and modifications as well as combinations of the disclosed embodiments will be recognized by a person skilled in the art. The invention is only restricted by the claims below.

10 The following detailed description of the invention is given with reference to the accompanying drawings, in which FIG. 1 is a perspective view of a subscriber terminal according to the invention; FIG. 2 is a front view of the subscriber terminal; FIG. 3 is a side view of the subscriber terminal; and FIG. 4 is a cross-sectional view of the subscriber terminal.

15 FIG. 1 shows a perspective view of a subscriber terminal 100.

20 FIG. 2 shows a front view of the subscriber terminal 100.

25 FIG. 3 shows a side view of the subscriber terminal 100.

30 FIG. 4 shows a cross-sectional view of the subscriber terminal 100. The subscriber terminal 100 includes a housing 102 and a base 104. The housing 102 has a top surface 106 and a bottom surface 108. The base 104 is attached to the bottom surface 108 of the housing 102. The housing 102 has a front panel 110 and a back panel 112. The front panel 110 has a display 114 and a keypad 116. The back panel 112 has a power connector 118 and an antenna connector 120. The subscriber terminal 100 also includes a radio module 122 and a power supply module 124. The radio module 122 is connected to the keypad 116 and the antenna connector 120. The power supply module 124 is connected to the power connector 118 and the radio module 122. The radio module 122 includes a microcontroller 126 and a transceiver 128. The power supply module 124 includes a battery 130 and a regulator 132. The microcontroller 126 is connected to the transceiver 128 and the regulator 132. The transceiver 128 is connected to the antenna connector 120. The regulator 132 is connected to the power connector 118 and the radio module 122. The radio module 122 is also connected to the keypad 116.

35 FIG. 5 shows a perspective view of a subscriber terminal 100.

40 FIG. 6 shows a front view of the subscriber terminal 100.

45 FIG. 7 shows a side view of the subscriber terminal 100.

50 FIG. 8 shows a cross-sectional view of the subscriber terminal 100.

55 FIG. 9 shows a perspective view of a subscriber terminal 100.

60 FIG. 10 shows a front view of the subscriber terminal 100.

65 FIG. 11 shows a side view of the subscriber terminal 100.

70 FIG. 12 shows a cross-sectional view of the subscriber terminal 100.

75 FIG. 13 shows a perspective view of a subscriber terminal 100.

80 FIG. 14 shows a front view of the subscriber terminal 100.

85 FIG. 15 shows a side view of the subscriber terminal 100.

90 FIG. 16 shows a cross-sectional view of the subscriber terminal 100.

CLAIMS

1. A subscriber terminal arrangement in a telecommunication system utilizing radio in the local loop, characterised by a subscriber terminal comprising a low power radio part, a pulse code modulation (PCM) air interface, and a low power paging channel for the call set-up procedure, a power supply part, and a user terminal comprising a hand-set and a dialling device.
2. An arrangement according to claim 1, characterised by a standard (e.g. CCITT) line interface between the subscriber terminal and the user terminal, the interface supporting a ringing generator and a two-wire copper cable.
3. An arrangement according to claim 1, characterised by a simple two-wire connection between the subscriber terminal and the user terminal, the user terminal further including a piezoelectric ringer.
4. An arrangement according to claim 1, characterised in that the subscriber terminal and the user terminal are integrated in the same unit.
5. An arrangement according to any one of the preceding claims, characterised in that the power supply part is integrated in the subscriber terminal.
6. An arrangement according to claim 1, characterised in that the subscriber terminal includes an interface for connecting a number of user terminals, e.g. up to 4, 8, 16, 32 or more.
7. An arrangement according to any one of the preceding claims, characterised by concentration in the radio part for supporting a greater number of user terminals than the number of radio channels.
8. An arrangement according to any one of claims 1 to 5, characterised in that an omnidirectional antenna is connected directly to the user terminal.
9. An arrangement according to any one of claims 1 to 7, characterised in that a separate antenna is connected to the subscriber terminal, e.g. directly on the subscriber terminal or via lines to a window, wall or roof mounted antenna.
10. An arrangement according to any one of the preceding claims, characterised in that the power supply

part is connected to an independent power supply unit comprising a power generator, e.g. solar panels and/or a wind generator, rechargeable batteries, and a control unit for controlling the charging procedure.

- 5 11. An arrangement according to any one of the preceding claims, characterised in that the air interface is capable of supporting 64 kb/s PCM coding offering high quality audio, and/or variable data rates up to 64 kb/s.

10 12. An arrangement according to claim 11, characterised in that the air interface is capable of multiplexing several PCM channels offering hi-fi audio, or ISDN basic rate access (BRA).

15 13. An arrangement according to any one of claims 1-3, 5-7, and 9-12, characterised in that the RF unit of the radio part is integrated with an antenna, the RF unit being powered from the subscriber terminal by an antenna cable.

1/2




FIG. 2





FIG. 3

**SUBSTITUTE SHEET**




FIG. 4




FIG. 5

SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00503

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04Q 7/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04Q, H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE, DK, FI, NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0583233 A2 (HUGHES AIRCRAFT COMPANY), 16 February 1994 (16.02.94), column 6, line 4 - line 22; column 17, line 5 - line 12, abstract --	1-9,10
Y	GB 2230162 A (MITSUBISHI DENKI KABUSHIKI KAISHA), 10 October 1990 (10.10.90), page 5, line 18 - page 7, line 2 --	1-9,10
Y	US 5444867 A (KUNIYOSHI MARUI ET AL), 22 August 1995 (22.08.95), column 1, line 39 - line 54; column 2, line 16 - line 28 --	10

 Further documents are listed in the continuation of Box C. See patent family annex.

- * Special categories of cited documents:
- "A" document defining the general state of the art which is not considered to be of particular relevance
- "B" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
9 July 1997	12 -07- 1997
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No: +46 8 666 02 86	Authorized officer Peter Hedman Telephone No... +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00503

C (Continuation): DOCUMENTS CONSIDERED TO BE RELEVANT

Categor y*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9419877 A1 (TELEFONAKTIEBOLAGET LM ERICSSON), 1 Sept 1994 (01.09.94), page 7, line 13 - page 8, line 19; page 10, line 18 - line 29	1-6,8,9

INTERNATIONAL SEARCH REPORT

International application No.

PCT/ISA/210 (continuation of first sheet (1)) (July 1992)

International application No. PCT/SE/97/00503

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.: because they relate to subject matter not required to be searched by this Authority, namely:
2. Claims Nos.: 7, 11-13 because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
Neither the description, nor the claims comprise any characteristic details on how the arrangements mentioned in claims 7, 11, 12 and 13 are supposed to be realized.
3. Claims Nos.: because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

The additional search fees were accompanied by the applicant's protest.

No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

01/07/97

International application No.

PCT/SE 97/00503

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0583233 A2	16/02/94	AU 654444 B AU 4465293 A CA 2103986 A FI 933560 A JP 6177832 A KR 9612090 B US 5633873 A	03/11/94 17/02/94 14/02/94 14/02/94 24/06/94 12/09/96 27/05/97
GB 2230162 A	10/10/90	GB 2267797 A;B GB 2271914 A,B GB 2271915 A,B JP 2262730 A JP 7073385 B US 5054052 A	15/12/93 27/04/94 27/04/94 25/10/90 02/08/95 01/10/91
US 5444867 A	22/08/95	CA 2059189 A DE 69218465 D,T EP 0494780 A,B KR 9604319 B US 5584055 A US 5590414 A JP 4250757 A JP 4239249 A JP 4239250 A JP 4239251 A US 5367556 A	12/07/92 03/07/97 15/07/92 30/03/96 10/12/96 31/12/96 07/09/92 27/08/92 27/08/92 27/08/92 22/11/94
WO 9419877 A1	01/09/94	AU 5825294 A CA 2133735 A CN 1108450 A EP 0636290 A EP 0647302 A FI 944845 A JP 8507183 T NO 943926 A NZ 259444 A SE 9300495 A US 5464258 A US 5533027 A	14/09/94 17/08/94 13/09/95 01/02/95 12/04/95 14/10/94 30/07/96 17/10/94 24/06/97 17/08/94 07/11/95 02/07/96

EDUCATIONAL APPLICATIONS

100-
100-
100-

卷之三

1948-1949
1949-1950
1950-1951
1951-1952
1952-1953
1953-1954
1954-1955
1955-1956
1956-1957
1957-1958
1958-1959
1959-1960
1960-1961
1961-1962
1962-1963
1963-1964
1964-1965
1965-1966
1966-1967
1967-1968
1968-1969
1969-1970
1970-1971
1971-1972
1972-1973
1973-1974
1974-1975
1975-1976
1976-1977
1977-1978
1978-1979
1979-1980
1980-1981
1981-1982
1982-1983
1983-1984
1984-1985
1985-1986
1986-1987
1987-1988
1988-1989
1989-1990
1990-1991
1991-1992
1992-1993
1993-1994
1994-1995
1995-1996
1996-1997
1997-1998
1998-1999
1999-2000
2000-2001
2001-2002
2002-2003
2003-2004
2004-2005
2005-2006
2006-2007
2007-2008
2008-2009
2009-2010
2010-2011
2011-2012
2012-2013
2013-2014
2014-2015
2015-2016
2016-2017
2017-2018
2018-2019
2019-2020
2020-2021
2021-2022
2022-2023
2023-2024
2024-2025
2025-2026
2026-2027
2027-2028
2028-2029
2029-2030
2030-2031
2031-2032
2032-2033
2033-2034
2034-2035
2035-2036
2036-2037
2037-2038
2038-2039
2039-2040
2040-2041
2041-2042
2042-2043
2043-2044
2044-2045
2045-2046
2046-2047
2047-2048
2048-2049
2049-2050
2050-2051
2051-2052
2052-2053
2053-2054
2054-2055
2055-2056
2056-2057
2057-2058
2058-2059
2059-2060
2060-2061
2061-2062
2062-2063
2063-2064
2064-2065
2065-2066
2066-2067
2067-2068
2068-2069
2069-2070
2070-2071
2071-2072
2072-2073
2073-2074
2074-2075
2075-2076
2076-2077
2077-2078
2078-2079
2079-2080
2080-2081
2081-2082
2082-2083
2083-2084
2084-2085
2085-2086
2086-2087
2087-2088
2088-2089
2089-2090
2090-2091
2091-2092
2092-2093
2093-2094
2094-2095
2095-2096
2096-2097
2097-2098
2098-2099
2099-20100

• 17 • *Wittgenstein*

1. *Leucanthemum vulgare* L. (Fig. 1). - Annual or biennial; stem erect, branched, 1-2 m. tall; leaves opposite, deeply lobed, petioled; flowers white, in corymbose clusters.

1	1	1	1	1
2	2	2	2	2
3	3	3	3	3
4	4	4	4	4
5	5	5	5	5

This image shows a severely damaged document page. The paper is off-white with dark, irregular smudges and stains. There are faint, illegible markings scattered across the surface, possibly bleed-through from the reverse side of the page. A large, dark, irregular smudge is located near the top center. In the upper right quadrant, there is a faint rectangular outline with some internal markings that are too faded to be read. The overall appearance is that of a lost or severely damaged record.